



HFYH.EX3769 Chlorinated Polyvinyl Chloride Pipe

[Page Bottom](#)

Chlorinated Polyvinyl Chloride Pipe

[See General Information for Chlorinated Polyvinyl Chloride Pipe](#)

SPEARS MFG CO

EX3769

15853 OLDEN ST
SYLMAR, CA 91342 USA

FlameGuard chlorinated polyvinyl chloride (CPVC) pipe, for Underground Fire Service Mains, sizes 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, and 3 in. for working pressures not exceeding 175 psi.

[Last Updated](#) on 2009-06-02

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".



VIWT.EX3769 Chlorinated Polyvinyl Chloride Sprinkler Pipe and Fittings

[Page Bottom](#)

Chlorinated Polyvinyl Chloride Sprinkler Pipe and Fittings

[See General Information for Chlorinated Polyvinyl Chloride Sprinkler Pipe and Fittings](#)

SPEARS MFG CO

EX3769

15853 OLDEN ST
SYLMAR, CA 91342-1249 USA

FlameGuard CPVC pipe and fittings of the following types and sizes for rated pressure of 175 psig:

Description	Size(s), in.
Pipe	3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3
Cap, Coupling, 90 degrees Elbow,	3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3
45 degrees Elbow, Tee, Cross	
90 degree Street Elbow	3/4, 1, 1-1/4, 1-1/2, 2
Street Tee	3/4, 1, 1-1/4, 1-1/2, 2
Reducing Bushing	1 x 3/4; 1-1/4 x 3/4, 1; 1-1/2 x 3/4, 1, 1-1/4; 2 x 3/4, 1, 1-1/4, 1-1/2; 2-1/2 x 1-1/4, 1-1/2, 2; 3 x 2, 2-1/2
Reducing Coupling	1 x 3/4; 1-1/4 x 3/4, 1; 1-1/2 x 3/4, 1, 1-1/4; 2 x 3/4, 1, 1-1/4, 1-1/2; 2-1/2 x 1-1/2, 2;
90 degrees Reducing Elbow	1 x 3/4
Reducing Tee	1 x 1 x 3/4; 1-1/4 x 1-1/4 x 3/4, 1; 1-1/2 x 1-1/4 x 3/4, 1; 1-1/2 x 1-1/2 x 3/4, 1, 1-1/4, 2; 2 x 2 x 3/4, 1, 1-1/2; 2-1/2 x 2-1/2 x 1, 1-1/4, 1-1/2, 3 x 3 x 2, 2-1/2; 1 x 3/4 x 3/4, 1; 1-1/4 x 1 x 3/4, 1, 1-1/4; 3/4 x 3/4 x 1; 1-1/4 x 1-1/4 x 1-1/2; 2 x 2 x 2-1/2
Reducing Cross	1 x 1 x 3/4 x 3/4
Sprinkler Adapter (Slip)	3/4 x 1/2; 1 x 1/2, 3/4
Sprinkler Adapter (Spigot)	3/4 x 1/2; 1 x 1/2
Sprinkler Adapter Elbow	3/4 x 1/2; 1 x 1/2, 3/4; 1-1/4 x 1/2
Sprinkler Adapter Tee	3/4 x 3/4 x 1/2; 1 x 1 x 1/2, 1; 1/2x1/2x3/4, 1/2 x 1/2 x 1; 1 x 3/4 x 1/2; 1-1/4 x 1 x 1/2;

	1-1/4 x 1-1/4 x 1/2;
	1-1/2 x 1-1/4 x 1/2;
	1-1/2 x 1-1/2 x 1/2, 1;
	2 x 1-1/2 x 1/2; 2 x 2 x 1/2; 1 x 1/2 x 1
Sprinkler Adapter Cross	3/4x3/4x1/2x1/2, 1 x 1 x
	1/2 x 1/2, 1 x 1 x 3/4 x 3/4
Adjustable Drop Nipple (Slip and Spigot) (equivalent length is 0.75 ft)	3/4 x 1/2; 1 x 1/2
Female Threaded Adapter (Slip)	3/4, 1, 1-1/4, 1-1/2, 2
Unions	
Female Threaded Adapter (Spigot)	3/4, 1
Male Threaded Adapter,	3/4, 1, 1-1/4, 1-1/2,
Flange Adapter	2, 2-1/2, 3
Grooved Coupling Adapter	1-1/4, 1-1/2, 2, 2-1/2, 3
Gasket Sealed Sprinkler Head Adapter	1 x 1/2
Gasket Sealed Sprinkler Head Adapter - Stainless Steel Insert	1 x 1/2
22-1/2° Elbow (Socket x Socket)	3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3
22-1/2° Elbow (Spigot x Socket)	3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3
Male Adapter	3/4, 1, 1-1/4, 1-1/2, 2
SofTorque™ Gasketed Sprinkler Head Adapter (Socket x Plastic FPT)	1 x 1/2
QuickTorque™ Gasketed Sprinkler Head Adapter (Socket x Steel FPT)	1 x 1/2 in.

The pipe and fittings are for use in accordance with the manufacturer's installation and design manual dated October 4, 2010, Addendum No. 1C dated November 22, 2014, Addendum No. 2 dated February 25, 2015 and Addendum No. 3 dated November 4, 2015. The pipe and fittings are also intended for use in low-pressure dry pipe systems.

Last Updated on 2017-03-01

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".